KDA05EVF

KODIAK BLAST CHILLER
5 TRAYS 600 x 400 - GN 1/1
DIGITAL DISPLAY

VENIX SRL Via della Fornace, 49 - 31023 Castelminio di Resana (TV) - ITALY
P +39 (0) 423 420 477 / +39 (0) 423 723 608 - F +39 (0) 423 492 307
email: info@venix.it
www.venix.it

FUNCTIONAL CHARACTERISTICS	
Display	Digital
Supply	ELECTRIC
Number of evaporator motors	1
Evaporator Motor speeds	1
Number of condenser motors	2
Condenser Motor speeds	1
Min chamber temperature (°C)	-35 °C
Core probe	PTC
Chamber material	Fingerprint free co-laminated steel
Frame material	Fingerprint free co-laminated steel
Opening door	Right handle
Door gasket	Magnetic removable
Door frame	Heated inspectable
Insulation	CFC-HFC free HD Poliurethane 60mm
STANDARDS	
Certification	CE
TRAYS	
Trays rack	Wire PA-BIV 5/68
Max tray load	4 kg
DIMENSIONS	
Blast chiller size with handle WxDxH (mm)	760 x 670 x 895
Chamber gross volume (L)	101 L
Chamber usefull volume (L)	91 L
Unit weight (Kg)	82 kg
PACKAGING	
Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	810 x 740 x 1080
Unit weight with packaging (Kg)	97 kg
ELECTRICAL DATA	
COMPRESSOR 220-230V 1N~	
Power	1300kW/1500W
Frequency	50/60Hz

VENIX SRL Via della Fornace, 49 - 31023 Castelminio di Resana (TV) - ITALY
P +39 (0) 423 420 477 / +39 (0) 423 723 608 - F +39 (0) 423 492 307
email: info@venix.it
www.venix.it

Power supply	220-230V 1N~
Amperage	7A
Power cord req.	3G1,5
COMPRESSOR 200-208V 1N~	
Power	1300kW/1500W
Frequency	50/60Hz
Power supply	200-208V 1N~
Amperage	7,8A
Power cord req.	3G1,5
REFRIGERATION CIRCUIT	
Cooling capacity**	1870W (50Hz) 2350W (60Hz)
Cooling capacity per cycle (+90°C > +3°C)	20 kg
Freezing capacity per cycle (+90°C > -18°C)	13 kg
Regfrigerant	R452a
Regfrigerant load	0,5kg
Evaporator	Anti-corrosion coating
Climate class	5 (43°C)
Defrost	Evaporator Fan
CO2 equivalent	2,55 Tons
FUNCTIONS	
Blast chilling cycles	Soft / hard
Deep Freezing	Soft / hard
Temperature regulation	Core probe / Time
Storage	+3°C/-18° automatic
Fish sanification	Standard
Ice cream	Standard
Recipes	Standard
Thowing	Optional
CONNECTIVITY	
USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

ACCESSORIES	
Stacking kit (SQUERO)	SK43
Stacking kit (SAN GIORGIO SAN MARCO)	SK44
Heated core probe	Optional
UV sanitizer	UV01
Pvoting wheel kit h80	R80
Pvoting wheel kit h100	R100
Ice cream kit	IX13

VENIX SRL Via della Fornace, 49 - 31023 Castelminio di Resana (TV) - ITALY
P +39 (0) 423 420 477 / +39 (0) 423 723 608 - F +39 (0) 423 492 307
email: info@venix.it
www.venix.it