



SQDK02DGBD03S

SQUERO OVEN 2 TRAYS 600x400
DIGITAL 2,4" LCD CONTROL
AISI 304 sole



FUNCTIONAL CHARACTERISTICS

Display	LCD
Supply	ELECTRICAL
Cooking type	STATIC
Max cooking temperature (°C)	400°C
Core probe	-
Cooking chamber material	AISI 304
Opening door	Flap door
Sole	AISI 304
Chimney	50 mm motorized
Boiler	Boiler
Air injection	V-dry

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays	2 x PA 600x400
Max tray load	5 kg

DIMENSIONS

Oven size with handle WxDxH (mm)	937 x 1207 x 447 mm
Oven size without handle WxDxH (mm)	937 x 1160 x 447 mm
Chamber size WxDxH (mm)	606 x 941 x 225 mm
Unit weight (Kg)	81,6 kg

PACKAGING

Packaging	Pallet + Carton Box
Packaging size WxDxH (mm)	985 x 1245 x 560 mm

ELECTRICAL DATA

Power	6,1 kW
Frequency	50/60Hz
Power supply	380-415V 3N~/220-240V 3~/220-240V 1N~
Amperage	10,1A/16A/26,5A
Power cord req.	5G1,5/4G2,5/3G4

WATER CONNECTION REQUIREMENTS

Humidification Water inlet	3/4" M Gas threaded
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa

CONNECTIVITY

USB	USB 2.0
Bluetooth	-
Wi-Fi	STANDARD
Cloud	STANDARD

ACCESSORIES

Oven stand	TA9374H30X TA9374H40X-TA9374H40S TA9374H49X-TA9374H49S TA9374H70X-TA9374H70S TA9374H80X-TA9374H80S
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA