



SM05TCC

COMBI OVEN 5 TRAYS GN 1/1
7" CAPACITIVE TOUCH CONTROL
SELF CLEAN INTEGRATED



FUNCTIONAL CHARACTERISTICS

Display	7" CAPACITIVE TOUCH
Supply	ELECTRIC
Timer	-
Number of motors	1
Motor speeds	10
Max cooking temperature (°C)	260°C
Core probe	3 Points PT1000
Cooking chamber material	AISI304
Opening door	Right handle
Chimney	50 mm Motorized valve

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Sheet GA 5/75 Trolley rails
Max tray load	4kg

DIMENSIONS

Oven size with handle WxDxH (mm)	792 x 1029 x 781
Oven size without handle WxDxH (mm)	793 x 962 x 781
Chamber size WxDxH (mm)	460 x 630 x 452
Unit weight (Kg)	92

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	880 x 1110 x 956
Unit weight with packaging (Kg)	112
Crate packaging size (optional)	880 X 1110 X 960

ELECTRICAL DATA

HEATERS 9kW 50/60Hz	
Power	9,4kW
Frequency	50/60Hz
Power supply	380-415V 3N~/220-240V 3~
Amperage	14,95A / 24,2A
Power cord req.	5G1,5/ 4G4

WATER CONNECTION REQUIREMENTS

Humidification/ Washing Water Inlet	3/4" GAS
Water drain	50 mm
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa

CONSUMPTION

Humidification Water (L/h)	2l/h max consumption
Rinse Water @2barG	17,8l
Short Washing Water @2barG	33,6l
Long Washing Water @2barG	70l
Short Washing Detergent *	234,4g
Long Washing Detergent *	334,8g

CONNECTIVITY

USB	USB 2.0
Bluetooth	-
Ethernet RJ45	-
Wi-Fi	Standard
Cloud	Available as Optional

ACCESSORIES

Self clean system kit	S1
Oven stand	TA7984H17X TA7984H30X TA7984H40S-TA7984H40X TA7984H49S-TA7984H49X TA7984H70S-TA7984H70X TA7984H80S-TA7984H80X
Hood (Air)	POSGMAF1 POSGMAF2
Hood (Water)	POSGMWF1 POSGMWF2
External Core Probe	CP5 (020SON0007)
Sous Vide Core Probe	CP4 (020SON0010)
Proofer	CA7912
Stacking kit for 2 ovens	SKSG15 SKSG85
Smoker	SMK02

Bast Chiller	ASP05
Blast chiller stacking kit	SK16
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6KG	DT2
Detergent10KG	DT4