



SM12TCC

COMBI OVEN 12 TRAYS GN 1/1
7" CAPACITIVE TOUCH CONTROL
SELF CLEAN INTEGRATED



FUNCTIONAL CHARACTERISTICS

| | |
|------------------------------|-----------------------|
| Display | 7" CAPACITIVE TOUCH |
| Supply | ELECTRIC |
| Timer | - |
| Number of motors | 3 |
| Motor speeds | 10 |
| Max cooking temperature (°C) | 260°C |
| Core probe | 3 Points PT1000 |
| Cooking chamber material | AISI304 |
| Opening door | Right handle |
| Chimney | 50 mm Motorized valve |

STANDARDS

| | |
|---------------|----|
| Certification | CE |
|---------------|----|

TRAYS

| | |
|---------------|----------------|
| Trays rack | Sheet GA 12/75 |
| Max tray load | 4kg |

DIMENSIONS

| | |
|-------------------------------------|-------------------|
| Oven size with handle WxDxH (mm) | 792 x 1021 x 1277 |
| Oven size without handle WxDxH (mm) | 793 x 954 x 1277 |
| Chamber size WxDxH (mm) | 460 x 630 x 948 |
| Unit weight (Kg) | 134 |

PACKAGING

| | |
|---------------------------------|---------------------|
| Packaging | PALLET + CARTON BOX |
| Packaging size WxDxH (mm) | 880 x 1110 x 1456 |
| Unit weight with packaging (Kg) | 150 |
| Crate packaging size (optional) | 880 X 1110 X 1458 |

ELECTRICAL DATA

HEATERS 5kW 50/60Hz

| | |
|-----------------|--------------------------|
| Power | 16,1kW |
| Frequency | 50/60Hz |
| Power supply | 380-415V 3N~/220-240V 3~ |
| Amperage | 26,6A / 41,8A |
| Power cord req. | 5G4/4G6 |

| HEATERS 6,5kW 50/60Hz | |
|------------------------------|--------------|
| Power | 19kW |
| Frequency | 50/60Hz |
| Power supply | 380-415V 3N~ |
| Amperage | 30,8A |
| Power cord req. | 5G4 |

WATER CONNECTION REQUIREMENTS

| | |
|--------------------------------------|-------------|
| Humidification / Washing Water Inlet | 3/4" GAS |
| Water drain | 50 mm |
| Max water hardness | 5°f |
| Water pressure requirement min-max | 150-200 kPa |

CONSUMPTION

| | |
|----------------------------|------------------------|
| Humidification Water (L/h) | 6,1l/h max consumption |
| Rinse Water @2barG | 17,8l |
| Short Washing Water @2barG | 35l |
| Long Washing Water @2barG | 71,8l |
| Short Washing Detergent * | 234,4g |
| Long Washing Detergent * | 334,8g |

CONNECTIVITY

| | |
|---------------|-----------------------|
| USB | USB 2.0 |
| Bluetooth | - |
| Ethernet RJ45 | - |
| Wi-Fi | Standard |
| Cloud | Available as Optional |

ACCESSORIES

| | |
|-----------------------|--|
| Self clean system kit | S1 |
| Oven stand | TA7984H17X TA7984H30X TA7984H40S-TA7984H40X TA7984H49S-TA7984H49X TA7984H70S-TA7984H70X TA7984H80S-TA7984H80X |
| Hood (Air) | POSGMAF1 POSGMAF2 |
| Hood (Water) | POSGMWF1 POSGMWF2 |

| | |
|----------------------------|------------------|
| External Core Probe | CP5 (020SON0007) |
| Sous Vide Core Probe | CP4 (020SON0010) |
| Proofer | CA7912 |
| Stacking kit for 2 ovens | SKSG15 SKSG85 |
| Smoker | SMK02 |
| Bast Chiller | ASP05 |
| Blast chiller stacking kit | SK16 |
| Water softner cover | WS10 |
| Water softner 6800L | WS11 |
| Water softner 12000L | WS12 |
| Water pressure adapter | WPA |
| Water shower kit | S1 |
| Detergent 6KG | DT2 |
| Detergent10KG | DT4 |