



SM20TCC

COMBI OVEN 20 TRAYS GN 1/1
7" CAPACITIVE TOUCH CONTROL
SELF CLEAN INTEGRATED



FUNCTIONAL CHARACTERISTICS

Display	7" CAPACITIVE TOUCH
Supply	ELECTRIC
Timer	-
Number of motors	4
Motor speeds	10
Max cooking temperature (°C)	260°C
Core probe	3 Points PT1000
Cooking chamber material	AISI304
Opening door	Right handle
Chimney	2 x 50 mm Motorized valve

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Trolley GA 20/66
Max tray load	4kg

DIMENSIONS

Oven size with handle WxDxH (mm)	1091 x 1006 x 1900
Oven size without handle WxDxH (mm)	1091 x 938 x 1900
Chamber size WxDxH (mm)	700 x 491 x 1496
Unit weight (Kg)	250

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	1150 x 1100 x 2115
Unit weight with packaging (Kg)	279
Crate packaging size (optional)	1150 x 1100 x 2107

ELECTRICAL DATA

HEATERS 6,75kW 50/60Hz 400V	
Power	28,6kW
Frequency	50/60Hz
Power supply	380-415V 3N~
Amperage	46,1A
Power cord req.	5G10

HEATERS 6,75kW 50/60Hz 400V / 230V	
Power	28,6kW
Frequency	50/60Hz
Power supply	380-415V 3N~/220-240V 3~
Amperage	46,1A / 73,8A
Power cord req.	5G10 / 4G25

HEATERS 6,5kW 50/60Hz 400V	
Power	25,5kW
Frequency	50/60Hz
Power supply	380-415V 3N~
Amperage	41,6A
Power cord req.	5G10

HEATERS 6,5kW 50/60Hz 400V / 230V	
Power	25,4kW
Frequency	50/60Hz
Power supply	380-415V 3N~/220-240V 3~
Amperage	41,6A / 65,97A
Power cord req.	5G10 / 4G25

HEATERS 5kW 50/60Hz 440V	
Power	26,2 kW
Frequency	50/60Hz
Power supply	440V 3~
Amperage	38,9A
Power cord req.	4G10

WATER CONNECTION REQUIREMENTS

Humidification / Washing Water Inlet	3/4" GAS
Water drain	2 x 50 mm
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa

CONSUMPTION

Humidification Water (L/h)	8,2l/h max consumption
Rinse Water @2barG	35,5l
Short Washing Water @2barG	66,6l
Long Washing Water @2barG	139l

Short Washing Detergent *	468,8g
Long Washing Detergent *	669,7g
CONNECTIVITY	
USB	USB 2.0
Bluetooth	-
Ethernet RJ45	-
Wi-Fi	Standard
Cloud	Available as Optional
ACCESSORIES	
Self clean system kit	-
Oven stand	-
Hood (Air)	-
Hood (Water)	POSLMWF1 POSLMWF2
External Core Probe	CP5 (020SON0007)
Sous Vide probe	CP4 (020SON0010)
Proofer	-
Stacking kit for 2 ovens	-
Smoker	SMK02
Bast Chiller	-
Blast chiller stacking kit	-
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6KG	DT2
Detergent10KG	DT4