



T03DIHAER

CONVECTION OVEN 3 TRAYS 600 x 400 - GN 1/1
DIGITAL CONTROL



FUNCTIONAL CHARACTERISTICS

Display	DIGITAL
Supply	ELECTRIC
Timer	-
Number of motors	1
Motor speeds	1 speed + reverse rotation
Max cooking temperature (°C)	260
Probe	Single point PT1000
Cooking chamber material	AISI 430
Opening door	Flap door
Chimney	20mm open
Humidification	Direct Injection
Air Injection	-
Version	Standard

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Wire PA-GA 3/75
Max tray load	3Kg

DIMENSIONS

Oven size with handle WxDxH (mm)	750 x 744 x 455
Oven size without handle WxDxH (mm)	750 x 697 x 455
Chamber size WxDxH (mm)	660 x 457 x 243
Unit weight (Kg)	36

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	774 x 764 x 582
Unit weight with packaging (Kg)	42
Crate packaging size (optional)	-

ELECTRICAL DATA

HEATERS 3,1kW 50/60Hz	
Power	3,4kW
Frequency	50/60 Hz
Power supply	220-240V ~
Amperage	14,7A
Power cord req.	3G1,5

WATER CONNECTION REQUIREMENTS

Humidification Water Inlet	3/4 M Gas threaded
Washing Water Inlet	-
Water drain	-
Max water hardness	5° f
Water pressure requirement min-max	150-200 kPa

CONSUMPTION

Humidification Water with solenoid valve	2l/h max consumption
Humidification Water with pump	-
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-

CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

ACCESSORIES

Self clean system kit	-
Oven stand	TA8058H60X - TA8058H60S TA8058H80X - TA8058H80S

Wheels kit for stand	R60B
Hood (Air)	-
Hood (Water)	POCK
Core Probe	-
Proofer	CA8008M0 CA8008MH CA8008DH
Stacking kit for 2 ovens	SKTC03N00
Smoker	-
Bast Chiller	ASP05 KDA03 KDA05
Blast chiller stacking kit	-
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	-
Detergent 750ML (for Self clean system or Manual shower kit)	-
Detergent 6 Kg	-
Detergent 10 Kg	-
Air reducer	RID07