



CA6008M0

CANNAREGIO PROOFER
for CONVECTION OVENS
8 TRAYS 460x340 - 450 x 330
MECHANICAL CONTROL



FUNCTIONAL CHARACTERISTICS

Overlapping oven	B043-B033-T043-T033-VE043
Display	Analogic
Supply	Electric
Timer	-
Max proofing temperature	60 [°C] 140 [°F]
Core probe	-
Cooking chamber material	AISI430
Opening door	Right handle

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Sheet PA 8/75 [mm](460x330 tray)
Max tray load	4 [kg]

DIMENSIONS

Size with handle WxDxH (mm)	600x678x876 [mm]
Chamber size WxDxH (mm)	505x611x783 [mm]
Unit weight (Kg)	28 [kg]

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	650x730x992 [mm]
Unit weight with packaging (Kg)	40 [kg]
Crate packaging size (optional)	-

ELECTRICAL DATA

Power	1,2kW
Frequency	50/60Hz
Power supply	220-240V 1N~
Amperage	5,3A
Power cord req.	3G1,5

WATER CONNECTION REQUIREMENTS

Humidification Water inlet	-
Water drain	-
Max water hardness	-
Water pressure requirement min-max	-

CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

ACCESSORIES

Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA