



CA6008MH

CANNAREGIO PROOFER
for CONVECTION OVENS
8 TRAYS 460x340 - 450x330
MECHANICAL CONTROL



FUNCTIONAL CHARACTERISTICS

Overlapping oven	B043-B033-T043-T033-VE043
Display	ANALOGIC
Supply	ELECTRIC
Timer	-
Max proofing temperature (°C)	60°C
Core probe	-
Cooking chamber material	AISI430
Opening door	Right handle

TRAYS

Trays rack	Sheet PA 8/75 (460x330 tray)
Max tray load	4kg

DIMENSIONS

Size with handle WxDxH (mm)	600 x 678 x 876
Chamber size WxDxH (mm)	505 x 611 x 783
Unit weight (Kg)	28

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	650 x 730 x 992
Unit weight with packaging (Kg)	40
Crate packaging size (optional)	-

ELECTRICAL DATA

Power	1,2kW
Frequency	50/60Hz
Power supply	220-240V 1N~
Amperage	5,3A
Power cord req.	3G1,5

WATER CONNECTION REQUIREMENTS

Humidification Water inlet	Male 3/4" GAS
Water drain	-
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa

CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

ACCESSORIES

Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA