



## KDA03EVF

KODIAK BLAST CHILLER  
3 TRAYS 600 x 400 - GN 1/1  
DIGITAL DISPLAY



## FUNCTIONAL CHARACTERISTICS

Display	Digital
Supply	ELECTRIC
Number of evaporator motors	1
Evaporator Motor speeds	1
Number of condenser motors	1
Condenser Motor speeds	1
Min chamber temperature (°C)	-35 °C
Core probe	PTC (optional)
Chamber material	Fingerprint free co-laminated steel
Frame material	Fingerprint free co-laminated steel
Opening door	Right handle
Door gasket	Magnetic removable
Door frame	Heated inspectable
Insulation	CFC-HFC free HD Poliurethane 60mm

## STANDARDS

Certification	CE
---------------	----

## TRAYS

Trays rack	Wire PA-BIV 3/85
Max tray load	4kg

## DIMENSIONS

Blast chiller size with handle WxDxH (mm)	760 x 670 x 895
Chamber gross volume (L)	101 L
Chamber usefull volume (L)	91 L
Unit weight (Kg)	77 kg

## PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	810 x 740 x 1080
Unit weight with packaging (Kg)	92 kg

## ELECTRICAL DATA

COMPRESSOR 220-230V 1N~2 50/60HZ	
Power	0,83kW/0,972kW
Frequency	50/60Hz
Power supply	220-230V 1N~
Amperage	4,9A/5,12
Power cord req.	3G1,5

## REFRIGERATION CIRCUIT

Cooling capacity**	1125W (50Hz) 1316W (60Hz)
Cooling capacity per cycle (+90°C > +3°C)	10 kg
Freezing capacity per cycle (+90°C > -18°C)	6 kg
Refrigerant	R452a
Refrigerant load	0,5 kg
Evaporator	Anti-corrosion coating
Climate class	5 (43°C)
Defrost	Evaporator Fan
CO2 equivalent	1,96 Tons

## FUNCTIONS

Blast chilling cycles	Soft / hard
Deep Freezing	Soft / hard
Temperature regulation	Core probe / Time
Storage	+3°C/-18° automatic
Fish sanitification	Not available
Ice cream	Not available
Recipes	Not available
Thowing	Not available

## CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

## ACCESSORIES

Stacking kit (SQUERO)	SK46
Stacking kit (SAN GIORGIO SAN MARCO)	SK16
Heated core probe	Optional
UV sanitizer	UV01
Pvoting wheel kit h80	R80
Pvoting wheel kit h100	R100
Ice cream kit	IX13