



## PODKMWF1

### FUNCTIONAL CHARACTERISTICS

Control	ANALOGIC
Condenser	WATER
Filter	Grease filter
Supply	Electric
Number of motors	1
Motor speeds	2
Oven compatibility	SQDK01-SQDK02*

### STANDARDS

Certification	CE
---------------	----

\*stacking kit SKDK01-SKDK02 compulsory



## DIMENSIONS

Hood size WxDxH (mm)	937 x 892 x 323
Unit weight (kg)	31,5

## PACKAGING

Packaging	Carton box
Packaging size WxDxH (mm)	1030 x 960 x 496
Unit weight with packaging (Kg)	38,2

## ELECTRICAL DATA

Power	0,3kW
Frequency	50/60Hz
Power supply	220-240V 1N~
Amperage	1,5A
Power cord req.	3G1,5

## WATER CONNECTION REQUIREMENTS

Humidification Water Inlet	3/4" Gas M Threaded
Water drain	30 mm
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa

## CONSUMPTION

Eco mode water consumption	0 - 0,44 L/m
Power mode water consumption	0 - 0,89 L/m

## ACCESSORIES

Spare carbon filter cartridge	60FIL003 (2X)
Spare carbon filter kit	85FIL00006

