



## B043DIHAER

CONVECTION OVEN 4 TRAYS 460X340 - GN 2/3\*  
DIGITAL CONTROL

\*Optional tray rack support for GN 2/3



## FUNCTIONAL CHARACTERISTICS

Display	Digital
Supply	Electric
Timer	-
Number of motors	1
Motor speeds	1 SPEED WITH REVERSE ROTATION
Max cooking temperature	260°C
Probe	Single point PT1000
Cooking chamber material	AISI 430
Opening door	Flap door
Chimney	20mm open
Humidification	Direct injection
Air Injection	-
Version	Standard

## STANDARDS

Certification	CE
---------------	----

## TRAYS

Trays rack	Wire PA 4/75
Max tray load	3Kg

## DIMENSIONS

Oven size with handle WxDxH (mm)	600 X 717 X 577
Oven size without handle WxDxH (mm)	600 X 670 X 577
Chamber size WxDxH (mm)	494 x 408 x 345
Unit weight (Kg)	40

## PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	640 x 764 x 693
Unit weight with packaging (Kg)	44
Crate packaging size (optional)	-

## ELECTRICAL DATA

Heaters 3.1kW 50/60 Hz	
Power	3,4kW
Frequency	50/60 Hz



Power supply	220-240V ~
Amperage	14,8A
Power cord req.	3G1,5

### WATER CONNECTION REQUIREMENTS

Humidification Water Inlet	3/4" M Gas threaded
Washing Water Inlet	-
Water drain	-
Max water hardness	5° f
Water pressure requirement min-max	150-200 kPa

### CONSUMPTION

Humidification Water with solenoid valve	2l/h max consumption
Humidification Water with pump	-
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-

### CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

### ACCESSORIES

Self clean system kit	-
Oven stand	TA6054H60X - TA6054H60S TA6054H80X - TA6054H80S
Wheels kit for stand	R100
Hood (Air)	-
Hood (Water)	POCK
Core probe	-
Proofer	CA6008M0 CA6008MH CA6088DH
Stacking kit for 2 ovens	SKBR43N00



Smoker	-
Blast chiller	KDA03 KDA05 ASP05
Blast chiller stacking kit	-
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	-
Detergent 6 Kg	-
Detergent 10 Kg	-
Air reducer	RID08

