



B04MIHAER

CONVECTION OVEN 4 TRAYS 600X400 - GN 1/1
MECHANICAL CONTROL



FUNCTIONAL CHARACTERISTICS

Display	Analogic
Supply	Electric
Timer	Linear
Number of motors	2
Motor speeds	1 speed + reverse rotation
Max cooking temperature	260°C
Probe	-
Cooking chamber material	AISI 430
Opening door	Flap door
Chimney	20mm open
Humidification	Direct injection
Air Injection	-
Version	Standard

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Wire PA-BIV 4/80 Wire PA 4/80 (optional)
Max tray load	4 kg

DIMENSIONS

Oven size with handle WxDxH (mm)	800 X 782 X 577
Oven size without handle WxDxH (mm)	800 X 735 X 577
Chamber size WxDxH (mm)	600 X 456 X 345
Unit weight (Kg)	58,6

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	850 X 855 X 697
Unit weight with packaging (Kg)	70,2
Crate packaging size (optional)	-

ELECTRICAL DATA

Heaters 3.1kW 50/60 Hz	
Power	6,7kW
Frequency	50/60 Hz



Power supply	380-415V 3N~/220-240V 3~/220-240V ~
Amperage	13,5A / 23,4A / 29,2A
Power cord req.	5G1,5/ 4G4/3G6

WATER CONNECTION REQUIREMENTS

Humidification Water Inlet	3/4" M Gas threaded
Washing Water Inlet	-
Water drain	-
Max water hardness	5° f
Water pressure requirement min-max	150-200 kPa

CONSUMPTION

Humidification Water with solenoid valve	0.8l/min max consumption
Humidification Water with pump	-
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-

CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

ACCESSORIES

Self clean system kit	-
Oven stand	TA8058H60X - TA8058H60S TA8058H80X - TA8058H80S
Wheels kit for stand	R100
Hood (Air)	-
Hood (Water)	POSSMWF1 POSSMWF2
Core Probe	-
Proofer	CA8008M0 CA8008MH CA8008DH



Stacking kit for 2 ovens	SKBR04N00
Smoker	SMK02
Blast Chiller	ASP05
Blast chiller stacking kit	-
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	-
Detergent 6 Kg	-
Detergent 10 Kg	-
Air reducer	RID08

