



CA8008M0

CANNAREGIO PROOFER
FOR CONVECTION OVENS
8 TRAYS 600X400 - GN 1/1
MECHANICAL CONTROL



FUNCTIONAL CHARACTERISTICS

Overlapping oven	B04-B03-T04-T03 VE04 - VE03
Display	ANALOGIC
Supply	ELECTRIC
Timer	-
Max proofing temperature (°C)	60°C
Core probe	-
Cooking chamber material	AISI430
Opening door	Double door

TRAYS

Trays rack	Sheet PA-BIV 8/75
Max tray load	4kg

DIMENSIONS

Size with handle WxDxH (mm)	800 x 678 x 866
Chamber size WxDxH (mm)	705 x 611 x 782
Unit weight (Kg)	36

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	650 x 730 x 992
Unit weight with packaging (Kg)	50
Crate packaging size (optional)	-

ELECTRICAL DATA

Power	2,4kW
Frequency	50/60Hz
Power supply	220-240V 1N~
Amperage	10,5A
Power cord req.	3G1,5

WATER CONNECTION REQUIREMENTS

Humidification Water inlet	-
Water drain	-
Max water hardness	-
Water pressure requirement min-max	-



CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

ACCESSORIES

Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA

