



## CA8212DH

CANNAREGIO PROOFER  
FOR CAMPIELLO OVENS  
6 TRAYS GN 2/1 - 600X400 - 12 TRAYS GN 1/1  
DIGITAL CONTROL



## FUNCTIONAL CHARACTERISTICS

|                               |   |
|-------------------------------|---|
| Overlapping oven              | CP04*-CP05*<br>CP06*-CP07*<br>CP10*-CP12* |
| Display                       | DIGITAL                                   |
| Supply                        | ELECTRIC                                  |
| Timer                         | -   |
| Max proofing temperature (°C) | 60°C                                      |
| Core probe                    | -   |
| Cooking chamber material      | AISI430                                   |
| Opening door                  | Double door                               |

## STANDARDS

|               |    |
|---------------|----|
| Certification | CE |
|---------------|----|

## TRAYS

|               |                   |
|---------------|-------------------|
| Trays rack    | Sheet PA-BIV 6/75 |
| Max tray load | 4kg               |

## DIMENSIONS

|                             |             |
|-----------------------------|-------------|
| Size with handle WxDxH (mm) | 820x890x705 |
| Chamber size WxDxH (mm)     | 610x810x560 |
| Unit weight (Kg)            | 52          |

## PACKAGING

|                                 |                     |
|---------------------------------|---------------------|
| Packaging                       | PALLET + CARTON BOX |
| Packaging size WxDxH (mm)       | 875x980x820         |
| Unit weight with packaging (Kg) | 62,8                |
| Crate packaging size (optional) | -                   |

## ELECTRICAL DATA

|                                  |              |
|----------------------------------|--------------|
| <b>HEATERS 1,3 kW (50/60 Hz)</b> |              |
| Power                            | 2,4kW        |
| Frequency                        | 50/60Hz      |
| Power supply                     | 220-240V 1N~ |
| Amperage                         | 10,5A        |
| Power cord req.                  | 3G1,5        |



## WATER CONNECTION REQUIREMENTS

|                                    |                          |
|------------------------------------|--------------------------|
| Humidification Water inlet         | Male 3/4" M Gas threaded |
| Water drain                        | -                        |
| Max water hardness                 | 5 °f                     |
| Water pressure requirement min-max | 150-200 kPa              |

## CONNECTIVITY

|           |   |
|-----------|---|
| USB       | - |
| Bluetooth | - |
| Wi-Fi     | - |
| Cloud     | - |

## ACCESSORIES

|                        |      |
|------------------------|------|
| Water softner cover    | WS10 |
| Water softner 6800L    | WS11 |
| Water softner 12000L   | WS12 |
| Water pressure adapter | WPA  |

