



## CP043M0N0

BAKERY OVEN 4 TRAYS 460X340 - GN 2/3\*  
MECHANICAL CONTROL

\*Optional tray rack support for GN 2/3



## FUNCTIONAL CHARACTERISTICS

|                          |                            |
|--------------------------|----------------------------|
| Display                  | Analogic                   |
| Supply                   | Electric                   |
| Timer                    | Linear scale               |
| Number of motors         | 1                          |
| Motor speeds             | 1 speed + reverse rotation |
| Max cooking temperature  | 260 °C                     |
| Core probe               | -                          |
| Cooking chamber material | AISI 430                   |
| Opening door             | Right handle               |
| Chimney                  | 20 mm open                 |
| Humidification           | Direct injection           |
| Air Injection            | -                          |
| Version                  | Standard                   |

## STANDARDS

|               |    |
|---------------|----|
| Certification | CE |
|---------------|----|

## TRAYS

|               |                 |
|---------------|-----------------|
| Trays rack    | Wire PA 4/75 mm |
| Max tray load | 3 Kg            |

## DIMENSIONS

|                                     |             |
|-------------------------------------|-------------|
| Oven size with handle WxDxH (mm)    | 614x767x602 |
| Oven size without handle WxDxH (mm) | 614x703x602 |
| Chamber size WxDxH (mm)             | 494x408x345 |
| Unit weight (kg)                    | 43,8        |

## PACKAGING

|                                 |                     |
|---------------------------------|---------------------|
| Packaging                       | PALLET + CARTON BOX |
| Packaging size WxDxH (mm)       | 640x810x733         |
| Unit weight with packaging (kg) | 56,4                |

## ELECTRICAL DATA

|                       |         |
|-----------------------|---------|
| Heaters 3.1kW 50/60Hz |         |
| Power                 | 3,4kW   |
| Frequency             | 50/60Hz |



|                 |            |
|-----------------|------------|
| Power supply    | 220-240V ~ |
| Amperage        | 14,8A      |
| Power cord req. | 3G1,5      |

### WATER CONNECTION REQUIREMENTS

|                                    |                     |
|------------------------------------|---------------------|
| Humidification Water Inlet         | 3/4" M Gas threaded |
| Washing Water Inlet                | -                   |
| Water drain                        | 30 mm               |
| Max water hardness                 | 5 ° f               |
| Water pressure requirement min-max | 150-200 kPa         |

### CONSUMPTION

|  |                         |
|--|-------------------------|
| Humidification Water with solenoid valve | 3,9 l/h max consumption |
| Humidification Water with pump           | -                       |
| Rinse Water @2barG                       | -                       |
| Short Washing Water @2barG               | -                       |
| Long Washing Water @2barG                | -                       |
| Short Washing Detergent *                | -                       |
| Long Washing Detergent *                 | -                       |

### CONNECTIVITY

|           |   |
|-----------|---|
| USB       | - |
| Bluetooth | - |
| Wi-Fi     | - |
| Cloud     | - |

### ACCESSORIES

|                       |   |
|-----------------------|---|
| Self clean system kit | -   |
| Oven stand            | TA8274H17X - TA8274H30X<br>TA8274H40X - TA8274H40S<br>TA8274H49X - TA8274H49S<br>TA8274H70X - TA8274H70S<br>TA8274H80X - TA8274H80S |
| Stand wheel kit       | R100  |
| Hood (Air)            | POCPMAF1<br>POCPMAF2  |
| Hood (Water)          | POCPMWF1<br>POCPMWF2  |



|                            |                                  |
|----------------------------|----------------------------------|
| External Core probe        | -                                |
| Sous vide probe            | -                                |
| Proofer                    | CA8212M0<br>CA8212MH<br>CA8212DH |
| Stacking kit for 2 ovens   | SKCP44N                          |
| Smoker                     | -                                |
| Blast Chiller              | -                                |
| Blast chiller stacking kit | -                                |
| Water softner cover        | WS10                             |
| Water softner 6800L        | WS11                             |
| Water softner 12000L       | WS12                             |
| Water pressure adapter     | WPA                              |
| Water shower kit           | S1                               |
| Detergent 6 Kg             | -                                |
| Detergent 10 Kg            | -                                |

