



CP05M0N0

COMBI OVEN 5 TRAYS GN 1/1
MECHANICAL CONTROL



FUNCTIONAL CHARACTERISTICS

Display	Analogic
Supply	Electric
Timer	Linear
Number of motors	2
Motor speeds	1 speed + reverse rotation
Max cooking temperature	260 °C
Core probe	-
Cooking chamber material	AISI 304
Opening door	Right handle
Chimney	50 [mm] open
Humidification	Direct injection
Air Injection	-
Version	Standard

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Wire GA 5/67 mm
Max tray load	4 kg

DIMENSIONS

Oven size with handle WxDxH (mm)	814x832x615
Oven size without handle WxDxH (mm)	814x768x616
Chamber size WxDxH (mm)	600x456x345
Unit weight (kg)	67,5

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	865x895x791
Unit weight with packaging (kg)	82,5
Crate packaging size (optional)	-

ELECTRICAL DATA

Heaters 5kW 50/60Hz	
Power	7,2kW
Frequency	50/60Hz
Power supply	380-415V 3N~ / 220-240V ~



Amperage	14,6A/31,3A
Power cord req.	5G1,5/3G6
WATER CONNECTION REQUIREMENTS	
Humidification Water Inlet	3/4" M Gas threaded
Washing Water Inlet	-
Water drain	-
Max water hardness	5 ° f
Water pressure requirement min-max	150-200 kPa
CONSUMPTION	
Humidification Water with solenoid valve	4,8 l/h max consumption
Humidification Water with pump	-
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-
CONNECTIVITY	
USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-
ACCESSORIES	
Self clean system kit	-
Oven stand	TA8274H17X - TA8274H30X TA8274H40X - TA8274H40S TA8274H49X - TA8274H49S TA8274H70X - TA8274H70S TA8274H80X - TA8274H80S
Stand wheel kit	R100
Hood (Air)	POCPMAF1 POCPMAF2
Hood (Water)	POCPMWF1 POCPMWF2
External Core probe	-
Sous vide probe	-
Proofer	CA8212M0 CA8212MH CA8212DH



Stacking kit for 2 ovens	SKCP44N
Smoker	-
Blast Chiller	-
Blast chiller stacking kit	-
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6 Kg	-
Detergent 10 Kg	-

