



KDA08EVF

KODIAK BLAST CHILLER
8 TRAYS 600X400 - GN 1/1
DIGITAL DISPLAY



FUNCTIONAL CHARACTERISTICS

Display	Digital
Supply	ELECTRIC
Number of evaporator motors	2
Evaporator Motor speeds	1
Number of condenser motors	1
Condenser Motor speeds	1
Min chamber temperature (°C)	-35 °C
Core probe	PTC
Chamber material	Fingerprint free co-laminated steel
Frame material	Fingerprint free co-laminated steel
Opening door	Right handle
Door gasket	Magnetic removable
Door frame	Heated inspectable
Insulation	CFC-HFC free HD Poliurethane 60mm

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Wire PA-BIV 8/74
Max tray load	4 kg

DIMENSIONS

Blast chiller size with handle WxDxH (mm)	790 x 760 x 1600
Chamber gross volume (L)	273 L
Chamber usefull volume (L)	249 L
Unit weight (Kg)	128 kg

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	830 x 800 x 1790
Unit weight with packaging (Kg)	148 kg



ELECTRICAL DATA

Compressor 230V 1N~ 50Hz

Power	2195W
Frequency	50Hz
Power supply	230V 1N~
Amperage	10,3A
Power cord req.	3G1,5

Compressor 230V 1N~ 60Hz

Power	2195W
Frequency	60Hz
Power supply	230V 1N~
Amperage	10,3A
Power cord req.	3G1,5

REFRIGERATION CIRCUIT

Cooling capacity**	3000W
Cooling capacity per cycle (+90°C > +3°C)	35 kg
Freezing capacity per cycle (+90°C > -18°C)	20 kg
Refrigerant	R452a
Refrigerant load	1,1kg
Evaporator	Anti-corrosion coating
Climate class	4 (38°C)
Defrost	Evaporator Fan
CO2 equivalent	3,92 Tons

FUNCTIONS

Blast chilling cycles	Soft / hard
Deep Freezing	Soft / hard
Temperature regulation	Core probe / Time
Storage	+3°C/-18° automatic
Fish sanification	-
Ice cream	-
Recipes	-
Thowing	-

**Evap-10°, Cond. 45



CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

ACCESSORIES

Stacking kit (SQUERO)	Not available
Stacking kit (SAN GIORGIO SAN MARCO)	Not available
Heated core probe	Optional
Pvoting wheel kit h80	R80
Pvoting wheel kit h100	R100
Ice cream kit	Not available

