



SQ04DG0

BAKERY OVEN 4 TRAYS 600x400 - GN 1/1
2,4" DIGITAL LCD CONTROL



FUNCTIONAL CHARACTERISTICS

Display	TFT 2,4" IPS
Supply	ELECTRIC
Timer	-
Number of motors	2
Motor speeds	5
Max cooking temperature (°C)	260°C
Core probe	Single point PT1000 (Optional)
Cooking chamber material	AISI 304
Opening door	Right handle
Chimney	50 mm open
Humidification	Direct injection
Air injection	V-Dry
Self-washing	-

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Wire PA-BIV 4/80 Sheet PA 4/85 (optional)
Max tray load	4 kg

DIMENSIONS

Oven size with handle WxDxH (mm)	937 X 885 X 715
Oven size without handle WxDxH (mm)	937 X 821 X 715
Chamber size WxDxH (mm)	660 X 490 X 452
Unit weight (Kg)	87

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	1020 X 970 X 868
Unit weight with packaging (Kg)	103
Crate packaging size (optional)	1020 X 970 X 873

ELECTRICAL DATA

HEATERS 5kW 50/60Hz	
Power	10,5kW
Frequency	50/60Hz



Power supply	380-415V 3N~
Amperage	16,80A
Power cord req.	5G2,5

HEATERS 5kW 50/60Hz

Power	10,5kW
Frequency	50/60Hz
Power supply	220-240V~
Amperage	45,73A
Power cord req.	3G16

HEATERS 6,5kW 50/60Hz

Power	12,5kW
Frequency	50/60Hz
Power supply	380-415V 3N~
Amperage	19,62A
Power cord req.	5G4

HEATERS 6,5kW 50/60Hz

Power	12,5kW
Frequency	50/60Hz
Power supply	220-240V ~
Amperage	58,78A
Power cord req.	3G16

WATER CONNECTION REQUIREMENTS

Humidification Water Inlet	3/4" GAS (male)
Washing Water Inlet	8mm quick fitting
Water drain	30 mm
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa

CONSUMPTION

Humidification Water (L/h)	4l/h max consumption
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-



CONNECTIVITY

USB	USB 2.0
Bluetooth	-
Wi-Fi	Standard
Cloud	Standard

ACCESSORIES

Self clean system kit	S20
Oven stand	TA9374H30X TA9374H40X - TA9374H40S TA9374H49X - TA9374H49S TA9374H70X - TA9374H70S TA9374H80X - TA9374H80S
Hood (Air)	POSQMAF1 POSQMAF2
Hood (Water)	POSQMWF1 POSQMWF2
External Core probe	CP5 (020SON0007)
Sous vide probe	CP4 (020SON0010)
Proofer	CA9308M0 CA9308MH CA9308DH CA9312M0 CA9312MH CA9312DH
Stacking kit for 2 ovens	SK42
Smoker	SMK02
Blast Chiller	KDA03 KDA05
Blast chiller stacking kit	SK43
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6KG	DT2
Detergent10KG	DT4

