



SQ053M0N0

COMBI OVEN 5 TRAYS - GN 2/3
MECHANICAL CONTROL
LINEAR SCALE



FUNCTIONAL CHARACTERISTICS

Display	ANALOGIC
Supply	ELECTRIC
Timer	Linear
Number of motors	1
Motor speeds	1
Max cooking temperature (°C)	260°C
Core probe	-
Cooking chamber material	AISI304
Opening door	Right handle
Chimney	30 mm open
Humidification	Direct injection
Air injection	-
Self-washing	-

TRAYS

Trays rack	Wire GA 5/67
Max tray load	4 kg

DIMENSIONS

Oven size with handle WxDxH (mm)	702 X 780 X 625
Oven size without handle WxDxH (mm)	702 X 718 X 625
Chamber size WxDxH (mm)	416 X 375 X 418
Unit weight (Kg)	55

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	765 X 850 X 785
Unit weight with packaging (Kg)	64
Crate packaging size (optional)	862 X 922 X 813

ELECTRICAL DATA

HEATERS 5kW 50/60Hz

Power	5,4kW
Frequency	50/60Hz
Power supply	380-415V 3N~/220-240V 3~/220-240V 1N~
Amperage	9,1A / 14,2A / 23,6A



Power cord req.	5G1 / 4G1,5 / 3G2,5
-----------------	---------------------

WATER CONNECTION REQUIREMENTS

Humidification Water Inlet	3/4" GAS
Washing Water Inlet	-
Water drain	30 mm
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa

CONSUMPTION

Humidification Water (L/h)	4,2l/h max consumption
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-

CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

ACCESSORIES

Self clean system kit	-
Oven stand	TA7066H80X - TA7066H80S
Hood (Air)	-
Hood (Water)	POCKMWN
Core Probe	-
Proofer	-
Stacking kit for 2 ovens	SK07
Smoker	SMK02
Blast Chiller	-
Blast chiller stacking kit	-
Water softner cover	WS10



Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6KG	-
Detergent 10KG	-

