



SQ0621AMVNO

COMBI GAS OVEN 6 TRAYS - GN 2/1 /
12 TRAYS - GN 1/1 OR 6 - 660X460*
MECHANICAL CONTROL

*Special tray rack support on request



FUNCTIONAL CHARACTERISTICS

Display	Analogic
Supply	Natural gas / GPL
Timer	Linear
Number of motors	2
Motor speeds	2
Max cooking temperature (°C)	260 °C
Core probe	-
Cooking chamber material	AISI304
Opening door	Right handle
Chimney	50 mm open
Humidification	Direct Injection
Air Injection	-
Version	Standard

STANDARDS

Certification	CB/GAR
---------------	--------

TRAYS

Trays rack	Sheet GA-BIV 6/80 mm
Max tray load	4 kg

DIMENSIONS

Oven size with handle WxDxH (mm)	964x1208x985 mm
Oven size without handle WxDxH (mm)	964x1143x985 mm
Chamber size WxDxH (mm)	660x770x612 mm
Unit weight (Kg)	129 kg

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	1055x1245x1082 mm
Unit weight with packaging (Kg)	150 kg
Crate packaging size (optional)	-

ELECTRICAL DATA

50Hz	
Power	0,4 kW
Frequency	50Hz



Power supply	220-240V 1N~
Amperage	1,82A
Power cord req.	3G1,5
60Hz	
Power	0,54 kW
Frequency	60Hz
Power supply	220-240V 1N~
Amperage	2,45A
Power cord req.	3G1,5
BURNER DATA	
G30-G31 Power (kW)	15 kW
G20 Power (kW)	15 kW
WATER CONNECTION REQUIREMENTS	
Humidification Water Inlet	3/4" M Gas threaded
Washing Water Inlet	8 mm quick fitting
Water drain	30 mm
Max water hardness	5 °f
Water pressure requirement min-max	150-200 kPa
CONSUMPTION	
Humidification Water (L/h)	22,4 l/h max consumption
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-
CONNECTIVITY	
USB	USB 2.0
Bluetooth	-
Wi-Fi	Yes
Cloud	Yes
ACCESSORIES	
Nozzle kit	85BRU00018 (Gas02)
Self clean system kit	-



Oven stand	-
Hood (Air)	-
Hood (Water)	-
External Core probe	-
Sous vide probe	-
Proofer	-
Stacking kit for 2 ovens	-
Smoker	SMK02
Blast chiller	-
Blast chiller stacking kit	-
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6 Kg	DT2
Detergent 10 Kg	DT4

