



SQ06TCC

BAKERY OVEN 6 TRAYS 600x400 GN 1/1
5" CAPACITIVE TOUCH CONTROL
SELF CLEANING INTEGRATED



FUNCTIONAL CHARACTERISTICS

Display	5" CAPACITIVE TOUCH
Supply	ELECTRIC
Timer	-
Number of motors	2
Motor speeds	2
Max cooking temperature (°C)	260°C
Core probe	Single point PT1000
Cooking chamber material	AISI304
Opening door	Right handle
Chimney	50 mm motorized
Humidification	Direct injection
Air injection	-
Self-washing	Automatic

STANDARDS

Certification	CE-CB
---------------	-------

TRAYS

Trays rack	Wire PA - BIV 6/80 Sheet PA 6/85 (optional)
Max tray load	4 Kg

DIMENSIONS

Oven size with handle WxDxH (mm)	937 X 885 X 875
Oven size without handle WxDxH (mm)	937 X 821 X 875
Chamber size WxDxH (mm)	660 X 490 X 612
Unit weight (Kg)	98

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	1020 X 970 X 1028
Unit weight with packaging (Kg)	115
Crate packaging size (optional)	1020 X 970 X 1033

ELECTRICAL DATA

HEATERS 5kW 50Hz	
Power	10,5kW
Frequency	50Hz



Power supply	380 - 415V 3N~/220 - 240V 3~
Amperage	16,73A/27,02A
Power cord req.	5G4 / 4G4
HEATERS 5kW 60Hz	
Power	10,8kW
Frequency	60Hz
Power supply	380 - 415V 3N~/220 - 240V 3~
Amperage	18,01A/28,17A
Power cord req.	5G4 / 4G4
HEATERS 6,5kW 50Hz	
Power	12,4kW
Frequency	50Hz
Power supply	380 - 415V 3N~/220 - 240V 3~
Amperage	19,56A/31,88A
Power cord req.	5G4 / 4G6
HEATERS 6,5kW 60Hz	
Power	12,7kW
Frequency	60Hz
Power supply	380 - 415V 3N~/220 - 240V 3~
Amperage	20,84A/33,03A
Power cord req.	5G4 / 4G6

WATER CONNECTION REQUIREMENTS

Humidification Water Inlet	3/4" GAS
Washing Water Inlet	8mm quick fitting
Water drain	30 mm
Max water hardness	5°f
Water pressure requirement min-max	150 - 200 kPa

CONSUMPTION

Humidification Water (L/h)	4l/h max consumption
Rinse Water @2barG	7,9l
Short Washing Water @2barG	24,9l
Long Washing Water @2barG	31,1l
Short Washing Detergent *	70,3g
Long Washing Detergent *	140,6g



CONNECTIVITY

USB	2.0
Bluetooth	-
Wi-Fi	-
Cloud	-

ACCESSORIES

Self clean system kit	-
Oven stand	TA9374H30X TA9374H40X - TA9374H40S TA9374H49X - TA9374H49S TA9374H70X - TA9374H70S TA9374H80X - TA9374H80S
Hood (Air)	POSQMAF1 POSQMAF2
Hood (Water)	POSQMWF1 POSQMWF2
Core Probe	-
Proofer	CA9308M0 CA9308MH CA9308DH CA9312M0 CA9312MH CA9312DH
Stacking kit for 2 ovens	SK42
Smoker	SMK02
Blast Chiller	KDA03 KDA05
Blast chiller stacking kit	SK43
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6KG	DT2
Detergent 10KG	DT4

