



## SQ10DG0

BAKERY OVEN 10 TRAYS 600x400 GN 1/1  
2,4" DIGITAL LCD CONTROL



## FUNCTIONAL CHARACTERISTICS

Display	TFT 2,4" IPS
Supply	ELECTRIC
Timer	-
Number of motors	3
Motor speeds	5
Max cooking temperature (°C)	260°C
Core probe	Single point PT1000 (Optional)
Cooking chamber material	AISI 304
Opening door	Right handle
Chimney	50 mm open
Humidification	Direct injection
Air injection	V-Dry
Self-washing	-

## STANDARDS

Certification	CE
---------------	----

## TRAYS

Trays rack	Wire PA-BIV 10/80 Sheet PA 10/85 (optional)
Max tray load	4 kg

## DIMENSIONS

Oven size with handle WxDxH (mm)	937 X 890 X 1211
Oven size without handle WxDxH (mm)	937 X 827 X 1211
Chamber size WxDxH (mm)	660 X 490 X 948
Unit weight (Kg)	135

## PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	1020 X 970 X 1363
Unit weight with packaging (Kg)	153
Crate packaging size (optional)	1020 X 970 X 1370

## ELECTRICAL DATA

HEATERS 5kW 50/60Hz	
Power	15,7kW
Frequency	50/60Hz



Power supply	380-415V 3N~
Amperage	25,03A
Power cord req.	5G4

#### HEATERS 5kW 50/60Hz

Power	15,7kW
Frequency	50/60Hz
Power supply	220-240V~
Amperage	68,43A
Power cord req.	3G25

#### HEATERS 6,5kW 50/60Hz

Power	18,6kW
Frequency	50/60Hz
Power supply	380 - 415V 3N~
Amperage	29,26A
Power cord req.	5G6

#### HEATERS 6,5kW 50/60Hz

Power	18,6kW
Frequency	50/60Hz
Power supply	220-240V~
Amperage	81,08A
Power cord req.	3G25

### WATER CONNECTION REQUIREMENTS

Humidification Water Inlet	3/4" GAS (male)
Washing Water Inlet	8mm quick fitting
Water drain	30 mm
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa

### CONSUMPTION

Humidification Water (L/h)	4l/h max consumption
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-



## CONNECTIVITY

USB	USB 2.0
Bluetooth	-
Wi-Fi	Standard
Cloud	Standard

## ACCESSORIES

Self clean system kit	S20
Oven stand	TA9374H30X TA9374H40X - TA9374H40S TA9374H49X - TA9374H49S TA9374H70X - TA9374H70S TA9374H80X - TA9374H80S
Hood (Air)	POSQMAF1 POSQMAF2
Hood (Water)	POSQMWF1 POSQMWF2
External Core probe	CP5 (020SON0007)
Sous vide probe	CP4 (020SON0010)
Proofer	CA9308M0 CA9308MH CA9308DH CA9312M0 CA9312MH CA9312DH
Stacking kit for 2 ovens	SK42
Smoker	SMK02
Blast Chiller	KDA03 KDA05
Blast chiller stacking kit	SK43
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6KG	DT2
Detergent10KG	DT4

