



## SQ10M0G0

BAKERY OVEN 10 TRAYS 600X400 - GN 1/1  
MECHANICAL CONTROL  
LOGARITHMIC SCALE



## FUNCTIONAL CHARACTERISTICS

|                              |                  |
|------------------------------|------------------|
| Display                      | MECHANICAL       |
| Supply                       | ELECTRIC         |
| Timer                        | Logarithmic      |
| Number of motors             | 3                |
| Motor speeds                 | 1                |
| Max cooking temperature (°C) | 260°C            |
| Core probe                   | -                |
| Cooking chamber material     | AISI304          |
| Opening door                 | Right handle     |
| Chimney                      | 50 mm open       |
| Humidification               | Direct injection |
| Air injection                | -                |
| Self-washing                 | -                |

## STANDARDS

|               |         |
|---------------|---------|
| Certification | CE - CB |
|---------------|---------|

## TRAYS

|               |  |
|---------------|--|
| Trays rack    | Wire PA - BIV 10/80<br>Sheet PA 10/85 (optional) |
| Max tray load | 4 Kg   |

## DIMENSIONS

|                                     |                  |
|-------------------------------------|------------------|
| Oven size with handle WxDxH (mm)    | 937 X 890 X 1211 |
| Oven size without handle WxDxH (mm) | 937 X 827 X 1211 |
| Chamber size WxDxH (mm)             | 660 X 490 X 948  |
| Unit weight (Kg)                    | 135              |

## PACKAGING

|                                 |                     |
|---------------------------------|---------------------|
| Packaging                       | PALLET + CARTON BOX |
| Packaging size WxDxH (mm)       | 1020 X 970 X 1363   |
| Unit weight with packaging (Kg) | 153                 |
| Crate packaging size (optional) | 1020 X 970 X 1370   |

## ELECTRICAL DATA

|                  |              |
|------------------|--------------|
| HEATERS 5kW 50Hz |              |
| Power            | 15,6kW       |
| Frequency        | 50Hz         |
| Power supply     | 380-415V 3N~ |



|                                      |  |
|--------------------------------------|--|
| Amperage                             | 24,5A  |
| Power cord req.                      | 5G4  |
| <b>HEATERS 6,5kW 50Hz</b>            |  |
| Power                                | 18,5kW   |
| Frequency                            | 50Hz   |
| Power supply                         | 380-415V 3N~   |
| Amperage                             | 28,7A  |
| Power cord req.                      | 5G6  |
| <b>WATER CONNECTION REQUIREMENTS</b> |  |
| Humidification Water Inlet           | 3/4" GAS   |
| Washing Water Inlet                  | 8mm quick fitting  |
| Water drain                          | 30 mm  |
| Max water hardness                   | 5°f  |
| Water pressure requirement min-max   | 150-200 kPa  |
| <b>CONSUMPTION</b>                   |  |
| Humidification Water (L/h)           | 11,8l/h max consumption  |
| Rinse Water @2barG                   | -  |
| Short Washing Water @2barG           | -  |
| Long Washing Water @2barG            | -  |
| Short Washing Detergent *            | -  |
| Long Washing Detergent *             | -  |
| <b>CONNECTIVITY</b>                  |  |
| USB                                  | -  |
| Bluetooth                            | -  |
| Wi-Fi                                | -  |
| Cloud                                | -  |
| <b>ACCESSORIES</b>                   |  |
| Self clean system kit                | -  |
| Oven stand                           | TA9374H30X<br>TA9374H40X - TA9374H40S<br>TA9374H49X - TA9374H49S<br>TA9374H70X - TA9374H70S<br>TA9374H80X - TA9374H80S |
| Hood (Air)                           | POSQMAF1<br>POSQMAF2   |
| Hood (Water)                         | POSQMWF1<br>POSQMWF2   |



|                            |  |
|----------------------------|--|
| Core Probe                 | -  |
| Proofer                    | CA9308M0<br>CA9308MH<br>CA9308DH<br>CA9312M0<br>CA9312MH<br>CA9312DH |
| Stacking kit for 2 ovens   | SK42   |
| Smoker                     | SMK02  |
| Blast Chiller              | KDA03<br>KDA05   |
| Blast chiller stacking kit | SK43   |
| Water softner cover        | WS10   |
| Water softner 6800L        | WS11   |
| Water softner 12000L       | WS12   |
| Water pressure adapter     | WPA  |
| Water shower kit           | S1   |
| Detergent 6KG              | DT2  |
| Detergent10KG              | DT4  |

