



SQ12ADGC

GAS COMBI OVEN 12 TRAYS - GN 1/1
2,4" DIGITAL LCD CONTROL
SELF CLEAN INTEGRATED



FUNCTIONAL CHARACTERISTICS

| | |
|------------------------------|---------------------|
| Display | 2,4" LCD IPS |
| Supply | Natural gas / GPL |
| Timer | - |
| Number of motors | 3 |
| Motor speeds | 2 |
| Max cooking temperature (°C) | 260 °C |
| Core probe | Single point PT1000 |
| Cooking chamber material | AISI304 |
| Opening door | Right handle |
| Chimney | 50 mm open |
| Humidification | Direct Injection |
| Air Injection | - |
| Version | Standard |

STANDARDS

| | |
|---------------|-----------|
| Certification | CE-GAR-CB |
|---------------|-----------|

TRAYS

| | |
|---------------|------------------|
| Trays rack | Wire GA 12/70 mm |
| Max tray load | 4 kg |

DIMENSIONS

| | |
|-------------------------------------|--------------|
| Oven size with handle WxDxH (mm) | 939x933x1321 |
| Oven size without handle WxDxH (mm) | 939x868x1321 |
| Chamber size WxDxH (mm) | 660x486x948 |
| Unit weight (Kg) | 164 |

PACKAGING

| | |
|---------------------------------|---------------------|
| Packaging | PALLET + CARTON BOX |
| Packaging size WxDxH (mm) | 1020x970x1422 |
| Unit weight with packaging (Kg) | 187 |
| Crate packaging size (optional) | - |

ELECTRICAL DATA

| | |
|--------------|--------------|
| 50Hz | |
| Power | 0,58kW |
| Frequency | 50Hz |
| Power supply | 220-240V 1N~ |



| | |
|--------------------------------------|-------------------------|
| Amperage | 2,64A |
| Power cord req. | 3G1,5 |
| 60Hz | |
| Power | 0,79 kW |
| Frequency | 60Hz |
| Power supply | 220-240V 1N~ |
| Amperage | 3,59A |
| Power cord req. | 3G1,5 |
| BURNER DATA | |
| G30-G31 POWER (KW) | 20 |
| G20 POWER (KW) | 20 |
| WATER CONNECTION REQUIREMENTS | |
| Humidification Water Inlet | 3/4" M Gas threaded |
| Washing Water Inlet | 8mm quick fitting |
| Water drain | 30 mm |
| Max water hardness | 5°f |
| Water pressure requirement min-max | 150-200 kPa |
| CONSUMPTION | |
| Humidification Water (L/h) | 23,6l/h max consumption |
| Rinse Water @2barG | 7,9l |
| Short Washing Water @2barG | 29,8l |
| Long Washing Water @2barG | 37,1l |
| Short Washing Detergent * | 255 g |
| Long Washing Detergent * | 511 g |
| CONNECTIVITY | |
| USB | USB 2.0 |
| Bluetooth | - |
| Wi-Fi | Yes |
| Cloud | Yes |
| ACCESSORIES | |
| Nozzle kit | 85BRU00019 (GAS03) |
| Self clean system kit | - |



| | |
|----------------------------|--|
| Oven stand | TA9374H30X TA9374H40X-TA9374H40S TA9374H49X-TA9374H49S TA9374H70X-TA9374H70S TA9374H80X-TA9374H80S |
| Hood (Air) | - |
| Hood (Water) | - |
| External Core probe | CP5 (020SON0007) |
| Sous vide probe | CP4 (020SON0010) |
| Proofer | CA9308M0 CA9308MH CA9308DH CA9312M0 CA9312MH CA9312DH |
| Stacking kit for 2 ovens | - |
| Smoker | SMK02 |
| Blast chiller | KDA03 KDA05 |
| Blast chiller stacking kit | SK43 |
| Water softner cover | WS10 |
| Water softner 6800L | WS11 |
| Water softner 12000L | WS12 |
| Water pressure adapter | WPA |
| Water shower kit | S1 |
| Detergent 6KG | DT2 |
| Detergent 10KG | DT4 |

