



SQ12TCC



COMBI OVEN 12 TRAYS - GN 1/1
5" CAPACITIVE TOUCH CONTROL
SELF CLEANING INTEGRATED



FUNCTIONAL CHARACTERISTICS

Display	5" CAPACITIVE TOUCH
Supply	ELECTRIC
Timer	-
Number of motors	3
Motor speeds	2
Max cooking temperature (°C)	260°C
Core probe	Single point PT1000
Cooking chamber material	AISI304
Opening door	Right handle
Chimney	50 mm motorized
Humidification	Direct injection
Air injection	-
Self-washing	Automatic

STANDARDS

Certification	CE-CB
---------------	-------

TRAYS

Trays rack	Wire GA 12/70 Sheet GA 12/70 (optional)
Max tray load	4 kg

DIMENSIONS

Oven size with handle WxDxH (mm)	937 X 890 X 1211
Oven size without handle WxDxH (mm)	937 X 827 X 1211
Chamber size WxDxH (mm)	660 X 490 X 948
Unit weight (Kg)	135

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	1020 X 970 X 1363
Unit weight with packaging (Kg)	153
Crate packaging size (optional)	1020 X 970 X 1370

ELECTRICAL DATA

HEATERS 5kW 50Hz	
Power	15,7kW
Frequency	50Hz



Power supply	380-415V 3N~/220-240V 3~
Amperage	24,9A/40,38A
Power cord req.	5G4/4G10

HEATERS 5kW 60Hz

Power	16,2kW
Frequency	60Hz
Power supply	380-415V 3N~/220-240V 3~
Amperage	26,85A/42,09A
Power cord req.	5G4/4G10

HEATERS 6,5kW 50Hz

Power	18,6kW
Frequency	50Hz
Power supply	380-415V 3N~
Amperage	29,2A
Power cord req.	5G6

HEATERS 6,5kW 60Hz

Power	19,1kW
Frequency	60Hz
Power supply	380-415V 3N~
Amperage	31,1A
Power cord req.	5G6

WATER CONNECTION REQUIREMENTS

Humidification Water Inlet	3/4" GAS
Washing Water Inlet	8mm quick fitting
Water drain	30 mm
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa

CONSUMPTION

Humidification Water (L/h)	4l/h max consumption
Rinse Water @2barG	7,9l
Short Washing Water @2barG	24,9l
Long Washing Water @2barG	31,1l
Short Washing Detergent *	70,3g
Long Washing Detergent *	140,6g



CONNECTIVITY

USB	2.0
Bluetooth	-
Wi-Fi	-
Cloud	-

ACCESSORIES

Self clean system kit	-
Oven stand	TA9374H30X TA9374H40X - TA9374H40S TA9374H49X - TA9374H49S TA9374H70X - TA9374H70S TA9374H80X - TA9374H80S
Hood (Air)	POSQMAF1 POSQMAF2
Hood (Water)	POSQMWF1 POSQMWF2
Core Probe	-
Proofer	CA9308M0 CA9308MH CA9308DH CA9312M0 CA9312MH CA9312DH
Stacking kit for 2 ovens	SK42
Smoker	SMK02
Blast Chiller	KDA03 KDA05
Blast chiller stacking kit	SK43
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6KG	DT2
Detergent 10KG	DT4

