



## SQ40M0N0

COMBI OVEN 40 TRAYS GN 1/1 - 20 GN 2/1  
MECHANICAL CONTROL  
LINEAR SCALE



## FUNCTIONAL CHARACTERISTICS

Display	ANALOGIC
Supply	ELECTRIC
Timer	LINEAR
Number of motors	4
Motor speeds	1
Max cooking temperature (°C)	260°C
Core probe	-
Cooking chamber material	AISI304
Opening door	Right handle
Chimney	50 mm open
Humidification	Direct injection
Air injection	-
Self-washing	-

## STANDARDS

Certification	CE
---------------	----

## TRAYS

Trays rack	Trolley GA 40/66
Max tray load	4 kg

## DIMENSIONS

Oven size with handle WxDxH (mm)	1051 X 1248 X 1881
Oven size without handle WxDxH (mm)	1051 X 1184X 1900
Chamber size WxDxH (mm)	700 X 726 X 1496
Unit weight (Kg)	285,8

## PACKAGING

Packaging	PALLET + CRATE
Packaging size WxDxH (mm)	1150 X 1345 X 2060
Unit weight with packaging (Kg)	395

## ELECTRICAL DATA

### HEATERS 10,5KW 50/60 Hz Single power supply

Power	43,1kW
Frequency	50/60Hz



Power supply	380-415V 3N~
Amperage	65,97A
Power cord req.	5G25

### WATER CONNECTION REQUIREMENTS

Humidification Water Inlet	-
Washing Water Inlet	-
Water drain	-
Max water hardness	-
Water pressure requirement min-max	-

### CONSUMPTION

Humidification Water (L/h)	15,7l/h max consumption
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-

### CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

### ACCESSORIES

Self clean system kit	-
Oven stand	-
Hood (Air)	-
Hood (Water)	POSLMWF1 POSLMWF2
Core Probe	-
Proofer	-
Stacking kit for 2 ovens	-
Smoker	SMK02
Blast Chiller	-
Blast chiller stacking kit	-
Water softner cover	WS10



Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6KG	DT2
Detergent 10KG	DT4

