



T032M00AAR

CONVECTION OVEN 3 TRAYS 346X260
MECHANICAL CONTROL



FUNCTIONAL CHARACTERISTICS

Display	MECHANICAL
Supply	ELECTRIC
Timer	LINEAR
Number of motors	1
Motor speeds	1
Max cooking temperature (°C)	260
Probe	-
Cooking chamber material	AISI 430
Opening door	Flap door
Chimney	20mm open
Humidification	-
Air Injection	-
Version	Standard

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Wire PA 3/75
Max tray load	3Kg

DIMENSIONS

Oven size with handle WxDxH (mm)	465 x 570 x 455
Oven size without handle WxDxH (mm)	465 x 520 x 455
Chamber size WxDxH (mm)	379 x 338 x 245
Unit weight (Kg)	25

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	505 x 660 x 550
Unit weight with packaging (Kg)	30
Crate packaging size (optional)	-

ELECTRICAL DATA

Heaters 2,8kW 50Hz	
Power	2,9kW
Frequency	50 Hz
Power supply	220-240V ~



Amperage	12,6A
Power cord req.	3G1,5
Heaters 2,8kW 60Hz	
Power	2,9kW
Frequency	60Hz
Power supply	220-240V ~
Amperage	12,7A
Power cord req.	3G1,5

WATER CONNECTION REQUIREMENTS

Humidification Water Inlet	-
Washing Water Inlet	-
Water drain	-
Max water hardness	-
Water pressure requirement min-max	-

CONSUMPTION

Humidification Water with solenoid valve	-
Humidification Water with pump	-
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-

CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

ACCESSORIES

Self clean system kit	-
Oven stand	-
Wheels kit for stand	-
Hood (Air)	-
Hood (Water)	POCKMWN
Core probe	-



Proofer	CA6008M0 CA6008MH CA6008DH
Stacking kit for 2 ovens	SKTC32N00
Smoker	-
Blast chiller	-
Blast chiller stacking kit	-
Water softner cover	-
Water softner 6800L	-
Water softner 12000L	-
Water pressure adapter	-
Water shower kit	-
Detergent 750ML (for Self clean system or Manual shower kit)	-
Detergent 6 Kg	-
Detergent 10 Kg	-
Air reducer	-

