



T033M00AAR

CONVECTION OVEN 3 TRAYS 450X340 - GN 2/3*
MECHANICAL CONTROL

*Optional tray rack support for GN 2/3



FUNCTIONAL CHARACTERISTICS

Display	MECHANICAL
Supply	ELECTRIC
Timer	LINEAR
Number of motors	1
Motor speeds	1
Max cooking temperature (°C)	260
Probe	-
Cooking chamber material	AISI 430
Opening door	Flap door
Chimney	20mm open
Humidification	-
Air Injection	-
Version	Standard

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Wire PA 3/75 Wire GA 3/67
Max tray load	3Kg

DIMENSIONS

Oven size with handle WxDxH (mm)	560 x 636 x 455
Oven size without handle WxDxH (mm)	560 x 588 x 455
Chamber size WxDxH (mm)	474 x 404 x 245
Unit weight (Kg)	26

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	584 x 724 x 635
Unit weight with packaging (Kg)	31
Crate packaging size (optional)	-

ELECTRICAL DATA

Heaters 2,8kW 50Hz	
Power	2,9kW
Frequency	50 Hz



Power supply	220-240V ~
Amperage	12,6A
Power cord req.	3G1,5
Heaters 2,8kW 60Hz	
Power	2,9kW
Frequency	60Hz
Power supply	220-240V ~
Amperage	12,7A
Power cord req.	3G1,5
WATER CONNECTION REQUIREMENTS	
Humidification Water Inlet	-
Washing Water Inlet	-
Water drain	-
Max water hardness	-
Water pressure requirement min-max	-
CONSUMPTION	
Humidification Water with solenoid valve	-
Humidification Water with pump	-
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-
CONNECTIVITY	
USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-
ACCESSORIES	
Self clean system kit	-
Oven stand	TA6054H80S - TA6054H80X TA6054H60S - TA6054H60X
Wheels kit for stand	R100



Hood (Air)	CK01
Hood (Water)	-
Core probe	-
Proofer	CA6008M0 CA6008MH CA6008DH
Stacking kit for 2 ovens	SKTC33N00
Smoker	-
Blast chiller	ASP05 KDA03 KDA05
Blast chiller stacking kit	-
Water softner cover	-
Water softner 6800L	-
Water softner 12000L	-
Water pressure adapter	-
Water shower kit	-
Detergent 750ML (for Self clean system or Manual shower kit)	-
Detergent 6 Kg	-
Detergent 10 Kg	-
Air reducer	-

