



T043MIHAAR

CONVECTION OVEN 4 TRAYS 450X340 - GN 2/3*
MECHANICAL CONTROL

*Optional tray rack support for GN 2/3



FUNCTIONAL CHARACTERISTICS

Display	MECHANICAL
Supply	ELECTRIC
Timer	LINEAR
Number of motors	1 speed + reverse rotation
Motor speeds	1
Max cooking temperature (°C)	260
Probe	-
Cooking chamber material	AISI 430
Opening door	Flap door
Chimney	20mm open
Humidification	Direct Injection
Air Injection	-
Version	Standard

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Wire PA 4/75
Max tray load	3Kg

DIMENSIONS

Oven size with handle WxDxH (mm)	560 x 683 x 530
Oven size without handle WxDxH (mm)	560 x 639 x 530
Chamber size WxDxH (mm)	474 x 378 x 320
Unit weight (Kg)	32

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	584 x 724 x 680
Unit weight with packaging (Kg)	40
Crate packaging size (optional)	-

ELECTRICAL DATA

Heaters 2,8kW 50/60Hz	
Power	3kW
Frequency	50/60 Hz



Power supply	220-240V ~
Amperage	13,2A
Power cord req.	3G1,5

WATER CONNECTION REQUIREMENTS

Humidification Water Inlet	YES
Washing Water Inlet	-
Water drain	-
Max water hardness	5° f
Water pressure requirement min-max	150-200 kPa

CONSUMPTION

Humidification Water with solenoid valve	0.8l/min max consumption
Humidification Water with pump	-
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-

CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

ACCESSORIES

Self clean system kit	-
Oven stand	TA6054H80S - TA6054H80X TA6054H60S - TA6054H60X
Wheels kit for stand	R100
Hood (Air)	-
Hood (Water)	POCK
Core probe	-
Proofer	CA6008M0 CA6008MH CA6008DH
Stacking kit for 2 ovens	-



Smoker	-
Blast chiller	ASP05 KDA03 KDA05
Blast chiller stacking kit	-
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	-
Detergent 750ML (for Self clean system or Manual shower kit)	-
Detergent 6 Kg	-
Detergent 10 Kg	-
Air reducer	RID06

