



## VE043LTHAERC

4 TRAYS 460 X 340 / GN 2/3\*  
SELF CLEAN INTEGRATED

\*Special tray rack support on request



## FUNCTIONAL CHARACTERISTICS

Display	LCD 2,4" IPS
Supply	Electric
Timer	-
Number of motors	1
Motor speeds	5
Max cooking temperature	260°C
Core probe	-
Cooking chamber material	AISI 304
Opening door	Flap Door
Chimney	30mm open
Humidification	Direct injection
Air injection	-
Self-washing	Automatic

## STANDARDS

Certification	CE
---------------	----

## TRAYS

Trays rack	4 x PA WIRE 4/80 (460X340) OPT 4 x GA-BIV 4/80 GN2/3 PA 460X340
Max tray load	4kg

## DIMENSIONS

Oven size with handle WxDxH (mm)	600x790x560
Oven size without handle WxDxH (mm)	600x750x560
Chamber size WxDxH (mm)	495x420x345
Unit weight (kg)	50 kg

## PACKAGING

Packaging	Pallet + Carton box
Packaging size WxDxH (mm)	675x825x692
Unit weight with packaging (Kg)	60 kg

## ELECTRICAL DATA

HEATERS 3,1kW (50/60Hz)	
Power	3,4kW
Frequency	50/60Hz



Power supply	230V 1~
Amperage	15A
Power cord req.	3G1,5

### WATER CONNECTION REQUIREMENTS

Humidification Water inlet	3/4" M Gas threaded
Washing Water inlet	8mm quick fitting
Water drain	30mm
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa

### CONSUMPTION

Humidification Water	0-2,4 l/h
Rinse Water @2barG	7,9 l
Short Washing Water @2barG	24,9 l
Long Washing Water @2barG	31,1 l
Short Washing Detergent *	70 g
Long Washing Detergent *	140 g

### CONNECTIVITY

USB	USB 2.0
Bluetooth	-
Wi-Fi	Standard
Cloud	Standard

### ACCESSORIES

Oven stand	TA6054H80S-TA6054H80X TA6054H60S-TA6054H60X
Wheels kit for stand	R100
Hood (Air)	-
Hood (Water)	-
Core probe	-
Proofers	CA6008M0 CA6008MH CA6008DH
Stacking kit for 2 ovens	SK52
Smoker	SMK02
Blast chiller	-



Blast chiller stacking kit	-
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6KG	DT2
Detergent 10KG	DT4

