CA9308M0

PROOFER FOR SQUERO OVENS
8 TRAYS 600 x 400 - GN 1/1
MECHANICAL CONTROL

FUNCTIONAL CHARACTERISTICS	
Overlapping oven	SQ04* - SQ05* - SQ06* - SQ07* - SQ10* - SQ12* SQ04A* - SQ05A* - SQ06A* - SQ07A* - SQ10A* - SQ12A*
Display	Analogic
Supply	Electric
Timer	-
Max prooving temperature	60°C
Core probe	-
Cooking chamber material	AISI430
Opening door	Double door
STANDARDS	
Certification	CE

VENIX SRL Via della Fornace, 49 - 31023 Castelminio di Resana (TV) - ITALY
P +39 (0) 423 420 477 / +39 (0) 423 723 608 - F +39 (0) 423 492 307
email: info@venix.it
www.venix.it

TRAYS	
Trays rack	Sheet PA-BIV 8/75 mm
Max tray load	4kg
DIMENSIONS	
Size with handle WxDxH	935 x 803 x 867 mm
Chamber size WxDxH	817 x 736 x 782 mm
Unit weight	48kg
PACKAGING	
Packaging	Pallet + carton box
Packaging size WxDxH	975 x 840 x 993 mm
Unit weight with packaging	63kg
Crate packaging size (optional)	-
ELECTRICAL DATA	
Power	2,4kW
Frequency	50/60Hz
Power supply	220-240V 1N~
Amperage	10,5A
Power cord req.	3G1,5
WATER CONNECTION REQUIREMENTS	
Humidification Water Inlet	-
Water drain	-
Max water hardness	-
Water pressure requirement min-max	-
CONNECTIVITY	
USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-
ACCESSORIES	
Water softner cover	WS10
Water softner 6800l	WS11
Water softner 12000l	WS12
Water pressure adapter	WPA

VENIX SRL Via della Fornace, 49 - 31023 Castelminio di Resana (TV) - ITALY
P +39 (0) 423 420 477 / +39 (0) 423 723 608 - F +39 (0) 423 492 307
email: info@venix.it
www.venix.it









03.	TEMPERATURE SELECTOR
04.	LIGHT ON/OFF HEATING ELEMENT
07.	UNIPOTENTIAL TERMINAL
08.	COMPRESSION CABLE GLAND
16.	ON/OFF

VENIX SRL Via della Fornace, 49 - 31023 Castelminio di Resana (TV) - ITALY
P +39 (0) 423 420 477 / +39 (0) 423 723 608 - F +39 (0) 423 492 307
email: info@venix.it
www.venix.it