



CA8008DH

PROOFER FOR CONVECTION OVEN
8 TRAYS 600 x 400 - GN 1/1
DIGITAL CONTROL

FUNCTIONAL CHARACTERISTICS

Overlapping oven	B04* - B03* - T04* - T03*
Display	Digital
Supply	Electric
Timer	-
Max proofing temperature	60°C
Core probe	-
Cooking chamber material	AISI430
Opening door	Double door

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Sheet PA - BIV 8/75 mm
Max tray load	4kg



DIMENSIONS

Size with handle WxDxH	800 x 678 x 866 mm
Chamber size WxDxH	705 x 611 x 782 mm
Unit weight	36kg

PACKAGING

Packaging	Pallet + carton box
Packaging size WxDxH	850 x 765 x 988 mm
Unit weight with packaging	50kg
Crate packaging size (optional)	-

ELECTRICAL DATA

Power	2,4kW
Frequency	50/60Hz
Power supply	220-240V 1N~
Amperage	10,5A
Power cord req.	3G1,5

WATER CONNECTION REQUIREMENTS

Humidification Water Inlet	Male 3/4" M Gas threaded
Water drain	-
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa





CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

ACCESSORIES

Water softner cover	WS10
Water softner 6800l	WS11
Water softner 12000l	WS12
Water pressure adapter	WPA





06.	HUMIDIFY SOLENOID VALVE 3/4" BSP (GAS)
07.	UNIPOTENTIAL TERMINAL
08.	COMPRESSION CABLE GLAND
09.	DIGITAL CONTROL

