VNX06T7C

BAKERY OVEN 6 TRAYS 600x400 GN 1/1
7" CAPACITIVE TOUCH CONTROL
SELF CLEAN INTEGRATED

FUNCTIONAL CHARACTERISTICS	
Display	7" Capacitive IPS touch screen
Supply	Electric
Timer	-
Number of motors	2
Motor speeds	10
Max cooking temperature	260°C
Core probe	3 Points PT1000
Cooking chamber material	AISI304
Opening door	Right handle
Chimney	50mm Motorized valve
Humidification	Direct injection
Air injection	Dry Pro
Version	Standard
Self-washing	Automatic

VENIX SRL Via della Fornace, 49 - 31023 Castelminio di Resana (TV) - ITALY
P +39 (0) 423 420 477 / +39 (0) 423 723 608 - F +39 (0) 423 492 307
email: info@venix.it
www.venix.it

Feet	55mm (not adjustable)
Duty cycle	7/7 - 10 hours/day
Dotations	-
STANDARDS	
Certification	CE
TRAYS	
Trays rack (standard)	Sheet univ. 6/80mm
Trays rack (optional)	Sheet PA. 6/85mm or Trolley set-up
Max tray load	4kg
DIMENSIONS	
Oven size with handle WxDxH	788 x 1056 x 767 mm
Oven size without handle WxDxH	788 x 981 x 767 mm
Chamber size WxDxH	490 x 638 x 540 mm
Unit weight	114.6kg
PACKAGING	
Packaging	Pallet + carton box
Packaging size WxDxH	865 x 1115 x 939 mm
Unit weight with cage	130.8kg
ELECTRICAL DATA	
HEATERS 5kW 50/60Hz	
Power	11kW
Frequency	50/60Hz
Power supply	380-415V 3N~
Amperage	18.6A
Power cord req.	5G2.5
HEATERS 5kW 50/60Hz	
Power	11kW
Frequency	50/60Hz
Power supply	220-240V 1N~
Amperage	48A
Power cord req.	3G10
WATER CONNECTION REQUIREMENTS	
Humidification Water Inlet	3/4" GAS
Washing Water Inlet	3/4" GAS

VENIX SRL Via della Fornace, 49 - 31023 Castelminio di Resana (TV) - ITALY
P +39 (0) 423 420 477 / +39 (0) 423 723 608 - F +39 (0) 423 492 307
email: info@venix.it
www.venix.it

Water drain	30mm
Max water hardness	5°f
Water pressure requirement min-max	150-200kPa
CONSUMPTION	
Humidification Water	7,2l/h max consumption
Rinse Water @2barG	7,9l
Short Washing Water @2barG	24,9l
Long Washing Water @2barG	31,1l
Short Washing Detergent *	80g
Long Washing Detergent *	160g
CONNECTIVITY	
USB	USB 2.0
Bluetooth	-
Wi-Fi	Yes
Cloud	Yes
ACCESSORIES	
Self clean system kit	-
Oven stand	TAVNXH1000X - TAVNXH1000U TAVNXH10D1U
Wheels kit for stand	R100 H+76mm
Hood (Air)	-
Hood (Water)	-
Hood (Air/Water)	POVNXTWF1
External Core probe	CP32
Sous vide probe	CP34
Proofer	CA7912M0 - MH - DH
Stacking kit for 2 ovens	KIT00181
Stacking kit for stand/oven	KIT00210
Heat shield	-
Water tempering kit	-
Siphon kit	KIT00182
Smoker	SMK02
Blast chiller	AST05
Blast chiller stacking kit	SK55
Water softner cover	WS10

Water softner 6800l	WS11
Water softner 12000l	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6kg	DT2

VENIX SRL Via della Fornace, 49 - 31023 Castelminio di Resana (TV) - ITALY
P +39 (0) 423 420 477 / +39 (0) 423 723 608 - F +39 (0) 423 492 307
email: info@venix.it
www.venix.it

◆ Standard ◇ Optional - Not available

TYPE OF COOKINGS	
Convection cooking	30°C - 260°C / 86°F - 500°F
Combi cooking	30°C - 230°C / 86°F - 446°F
Steaming cooking	30°C - 130°C / 86°F - 266°F
Static cooking	-
Delta T cooking	5°C - 115°C Δ / 41 °F - 239 °F Δ
Core probe cooking	◆
Sous vide cooking	◆
Low temperature cooking	◆
DISPLAY AND CONNECTIVITY	
Type of display	5" CAPACITIVE IPS TOUCH SCREEN
Multi-language display	◆
Unit set F° or C°	◆
Venix cloud	◆
Wi-fi	◆
Ethernet port	◆
Web server	◆
Usb port	◆
SETTINGS	
Infinity time set	◆
Chimney set	MOTORIZED
Fan speed set	10
Dehumidification set	◆
Humidity set	0-100%
Preheat set	AUTOMATIC
RECIPE COOKING	
User recipes book	500
Factory recipes book	INCLUDED
Cooking cycles	10
Recipes with name and picture	◆
Fast recipe selection buttons	◆
SPECIAL CYCLE	
Multi-level mix ALL IN	◆
Multi-level mix ALL OUT	◆
Food regeneration	◆
Overnight cooking	◆
Overnight self clean	◆
Cook & hold	◆

VENIX SRL Via della Fornace, 49 - 31023 Castelminio di Resana (TV) - ITALY
P +39 (0) 423 420 477 / +39 (0) 423 723 608 - F +39 (0) 423 492 307
email: info@venix.it
www.venix.it

Multi-timer	◆
Routine program	◆
Proofing	◆
Fast Cooling	◆
Automatic washing system / Rinse	◆
Fast start	◆
Recipe scheduling	◆
Holding / Mass production	◆
TECHNICAL FEATURES	
Cooking chamber material	AISI 304
Second core probe	◇
Insertion of the trays	IN DEPTH
Fast loading Pro	◇
Glass door	TRIPLE
Easy clean internal glass	◆
High performance thermal insulation	◆
Break drop nebulizer	◆
Lightning	LED ON THE DOOR
Direct injection humidification	◆
Boiler humidification	-
Opening door	NOT REVERSIBLE (RIGHT HANDLE)
Reversing fan	◆
Heavy duty reversing fan	◆
Phase cut speed control	-
Inverter speed control	◆

VENIX SRL Via della Fornace, 49 - 31023 Castelminio di Resana (TV) - ITALY
P +39 (0) 423 420 477 / +39 (0) 423 723 608 - F +39 (0) 423 492 307
email: info@venix.it
www.venix.it









1.	USB CONNECTION
2.	TOUCH CONTROL
3.	SAFETY THERMOSTAT
4.	HOT VAPOUR CHIMNEY Ø50MM

5.	DRAIN PIPE Ø30MM
6.	POWER CORD
7.	DETERGENT INLET
8.	WATER IN-LET

VENIX SRL Via della Fornace, 49 - 31023 Castelminio di Resana (TV) - ITALY
P +39 (0) 423 420 477 / +39 (0) 423 723 608 - F +39 (0) 423 492 307
email: info@venix.it
www.venix.it